



DIGITAL THERMOMETER

7521.0030

Parameters:

- Temperature range: $-50^{\circ}\text{C} \sim +300^{\circ}\text{C} / -58^{\circ}\text{F} \sim +572^{\circ}\text{F}$
- Distinguishing rate: $0.1^{\circ} < 100^{\circ}$, otherwise 0.5°
- Accuracy: $\pm 1^{\circ}\text{C}$ ($\pm 2^{\circ}\text{F}$) between $-20^{\circ}\text{C} \sim +100^{\circ}\text{C}$
 $\pm 2^{\circ}\text{C}$ between $-40^{\circ}\text{C} \sim -20^{\circ}\text{C}$ and $100^{\circ}\text{C} \sim 200^{\circ}\text{C}$
Otherwise range for $\pm 5^{\circ}\text{C}$
- Ambient temperature: $-10^{\circ}\text{C} \sim +40^{\circ}\text{C}$
- Battery Power: DC1.5V 7# alkaline battery (optional)
- Probe Size: 125mm(L)
- Display size: 50x21.8mm
- Product size: 154.6x47.6x20mm

Functions:

- fold the probe to turn off the display;
- Switch between $^{\circ}\text{C}/^{\circ}\text{F}$.
- Data hold function, be convenient to read the right data.
- Maximum and minimum memory function.
- Sensor error display: Display "LL.L" when sensor open circuit or lower than measuring range; Display "HH.H" when sensor short circuit or higher than measuring range.

Operation description:

- $^{\circ}\text{C}/^{\circ}\text{F}$: Press " $^{\circ}\text{C}/^{\circ}\text{F}$ " button once to change the temperature unit.
- MAX/MIN: Press "MAX/MIN" button once to display the maximum temperature reading, then press "MAX/MIN" button again to display the minimum temperature reading, then press again to jump to normal temperature.
- HOLD: Press "HOLD" button once to retain reading, then press "HOLD" button again to release the HOLD function.
- No use for long time, pls take out the battery.
- The thermometer can not be used or put inside any oven or microwave.

