



INDICATIVE PRODUCT IMAGE

7265.1070

Product file

Type	Compact
Mounting	Wall
Code	BYWS302LA50P11
Range	BYWS
Version	Saddle
Noise	34.5 dBA 10 m
Condensation	Air
Net weight	81 kg
PED	0
Defrost	Hot gas
Expansion	Valve
Application	LBP
Refrigerant	R290

Dimensions

Width L	671 mm
Depth P	975 mm
Height H	828 mm

Absorptions

Power consumption	1295 W
Current consumption	7 A

Condenser

Fan-motors no.	1
Diameter	300 mm
Air flow	1200 m³/h


Unit cooler

Fan-motors no.	2
Diameter	200 mm
Air flow	1000 m³/h
Air throw	6.5 m


Compressor

Type	Hermetic
Compressors no.	2
Brand	EMBRACO
Voltage	230/1/50
Displacement	2 X 21 cm³

Technical data - BYWS302LA50P11 - 7265.1070



Technical data - BYWS302LA50P11 - 7265.1070



Refrigerating capacity table (W) - BYWS302LA50P11 - 7265.1070 - Refrigerant: R290

TA \ Tcella	-25 °C	-20 °C	-15 °C
25 °C	1411 (15.5 m³)	1684 (25.7 m³)	1988 (41.7 m³)
32 °C	1316 (10.3 m³)	1579 (18.2 m³)	1870 (29.4 m³)
38 °C	1232 (7.8 m³)	1483 (11.7 m³)	1759 (21.2 m³)
43 °C	1158 (6.1 m³)	1398 (9.1 m³)	1660 (14.9 m³)

Values referred to :

Suction gas : +20°C

Subcooling : 0K

Superheat : 100%

Compressor absorption :

Te -5°C (HBP); Tcond +50°C

Te -10°C (MBP); Tcond +50°C

Te -30°C (LBP); Tcond +50°C



INDICATIVE PRODUCT IMAGE

MECHANICAL PART MAIN COMPONENTS

- Hermetic compressors with thermal motor protection
- Condenser with Ø5mm tubes with internal spiral rifling
- Evaporator with Ø5/16" tubes with internal spiral rifling
- Electronic fan-motors on both condenser and evaporator
- Mechanical thermostatic valve supplied standard across the entire range
- Hot gas defrosting
- Evaporating water tray
- R290 refrigerant charge ≤ 150g per circuit

CONTROL CIRCUIT and ELECTRICAL PART

- Safety pressure switch on high pressure side
- Door micro-switch wired with cable L= 2.5
- Door heater cable on LT models (L = 2.5m)
- LED cold room light with cable L= 5m
- Power supply cable L= 2.5 m with wired electrical plug
- Industrial Plug (2P+E or 3P+N+E) 16 A
- Industrial Plug (2P+E) 32 A only on BEWx352MA80P11 and BEWx352LA60P11

ELECTRONIC CONTROL

- Electronic board that can be programmed according to different user requirements
- Connection cable for BMS (RTU Modbus Protocol) L=5 m
- integral control panel

STRUCTURE

- Self-supporting frame in galvanized metal sheet
- Easily removable housing for a rapid access to the components in case of inspection or maintenance
- Installation kit complete with screws and washers to secure the packaged system to the wall of the coldroom and sealing putty in strips for insulation

OPTIONAL ITEMS

- Plug-in insulation kits supplied separately for saddle models (WS): 100mm, 150mm, 200mm
- Extension cable kits L=5m and L=10m (coldroom light cable, door heater cable, micro-switch cable)
- Presetting for Master & Slave (cable L=5m)