



Self-contained ice maker up to 104 kg - Granular system

Position n°



Application fields

Hotel	••••••	Fish market	••••••
Restaurant	•••••	Supermarket	••••••
Fast food	• • • • • • •	SPA	••••••
Bar	••••••	Medical	••••••
Disco		Industry	

• Features & Plus

- Granular ice
- Low consumption (1 liter water / 1 kg ice) aircooled vers.
- Electromechanical functionning
- Extrernal structure AISI 304 Scotch Brite
- Evaporator AISI 304, auger AISI 303 made
- Air Cooling and Water Cooling systems
- Standard and special voltages
- Insulated retractable door
- ON-OFF switch
- Dust proof water basin
- Automatic water charge
- Easy cleaning thanks to rounded surfaces
- External protective filter, removable, easy to clean
- Removable side panels
- Internal bin insulation HCFC free
- Model in Tropical Class + 43 ° C
- Conformity to RoHS directive
- Adjustable Stainless Steel feet
- Undercounter model


• Prod. 24h

Air temp.	Water temp.	Prod. 24h kg
10° C	10° C	104
21° C	15° C	95
32° C	21° C	81





Self-contained ice maker up to 104 kg - Granular system



Connections

All measures are referred to the rear bottom-left corner (L-H- \varnothing)

- ① Water inlet: 105 mm - 135 mm - 3/4"
- ② Water outlet: 55 mm 140 mm 24 mm
- ③ Electrical connection: 115 mm - 220 mm

Working conditions

- Location: Indoor

	Min	Max
Ambient temperature	+10° C	+43° C
Water temperature	+3° C	+32° C
Voltage	-10%	+10%
Water inlet pressure	1bar (14 psi)	6bar (84 psi)

• Technical information

Production in 24h	95 kg
Store capacity, up to	19 kg
Cooling system	A - W
Refrigerant	R404A
Standard voltage	220-240 V ~ 50 Hz
Electrical consumption	550 W
Fuse	10 A
Water consumption	A: 1 l/kg
	W: 6,3 l/kg
Sizes (L-P-H mm)	496 - 660 - 685
Sizes with pack (L-P-H r	mm) 550 - 720 - 880
Net weight	59 kg
Gross weight	67 kg
Finish	AISI 304 stainless steel, scotch brite

All the technical information must be considered at the following conditions:



Sizes without feet



Ambient temperature +21° C



Water temperature +15° C



Electrical consumption at +43° C (standard voltage)

Models and specifications are subject to change without notice Rev. 00 - Issued January 2017